



# Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : Oil Well Pumping : High Slip - NEMA Design "D" - TEFC (IP55)

Frame : 284T  
 Output : 15 HP  
 Frequency : 60 Hz  
 Poles : 6  
 Full load speed : 1115 rpm  
 Slip : 7.08 %  
 Voltage : 208-230/460 V  
 Rated current : 40.8-36.9/18.5 A  
 Locked rotor current : 225/113 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 6.1  
 No-load current : 11.0/5.50 A  
 Full load torque : 69.7 lb.ft  
 Locked rotor torque : 300 %  
 Breakdown torque : 0 %  
 Design : D  
 Insulation class : F  
 Temperature rise : 80 K  
 Locked rotor time : 16 s (hot)  
 Service factor : 1.15  
 Duty cycle : S1  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : IP55  
 Approximate weight : 391 lb  
 Moment of inertia : 7.1992 sq.ft.lb  
 Noise level : 59 dB(A)

	D.E.	N.D.E.
Bearings	6311 C3	6211 C3
Regreasing interval	20000 h	20000 h
Grease amount	18 g	11 g

Load	Power factor	Efficiency (%)
100%	0.88	85.0
75%	0.85	86.0
50%	0.78	85.0

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #01512ES3EOW284T

Performed by

Checked