



# Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : Close Coupled Pump: Three-Phase - W22 "JP" Type - TEFC - High Efficiency

Frame : 215JP  
 Output : 15 HP  
 Frequency : 60 Hz  
 Poles : 2  
 Full load speed : 3490 rpm  
 Slip : 3.06 %  
 Voltage : 230/460 V  
 Rated current : 33.6/16.8 A  
 Locked rotor current : 212/106 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 6.3  
 No-load current : 8.80/4.40 A  
 Full load torque : 22.3 lb.ft  
 Locked rotor torque : 210 %  
 Breakdown torque : 250 %  
 Design : B  
 Insulation class : F  
 Temperature rise : 80 K  
 Locked rotor time : 15 s (hot)  
 Service factor : 1.15  
 Duty cycle : S1  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : IP55  
 Approximate weight : 163 lb  
 Moment of inertia : 0.64024 sq.ft.lb  
 Noise level : 72 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6309 Z-C3	6207 ZZ	100%	0.91	90.2
Regreasing interval	19000 h	---	75%	0.89	90.2
Grease amount	13 g	---	50%	0.84	89.5

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #01536EP3E215JP-W22

Performed by

Checked