



# Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : W22 NEMA Premium - Ball Bearings

Frame : 324/6T  
 Output : 20 HP  
 Frequency : 60 Hz  
 Poles : 8  
 Full load speed : 880 rpm  
 Slip : 2.22 %  
 Voltage : 208-230/460 V  
 Rated current : 62.6-56.6/28.3 A  
 Locked rotor current : 283/142 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 5.0  
 No-load current : 32.0/16.0 A  
 Full load torque : 118 lb.ft  
 Locked rotor torque : 190 %  
 Breakdown torque : 220 %  
 Design : B  
 Insulation class : F  
 Temperature rise : 80 K  
 Locked rotor time : 27 s (hot)  
 Service factor : 1.25  
 Duty cycle : S1  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : IP55  
 Approximate weight : 452 lb  
 Moment of inertia : 9.3650 sq.ft.lb  
 Noise level : 56 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6312 C3	6212 C3	100%	0.73	91.0
Regreasing interval	20000 h	20000 h	75%	0.66	91.0
Grease amount	21 g	13 g	50%	0.54	89.5

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #02009ET3E324T-W22

Performed by

Checked