



Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Close Coupled Pump: Three-Phase - W22 "JM" Type - TEFC - NEMA Premium

Frame : 284/6JM
 Output : 20 HP
 Frequency : 60 Hz
 Poles : 6
 Full load speed : 1175 rpm
 Slip : 2.08 %
 Voltage : 208-230/460 V
 Rated current : 53.5-48.4/24.2 A
 Locked rotor current : 300/150 A
 Locked rotor current (I_L/I_n) : 6.2
 No-load current : 19.0/9.50 A
 Full load torque : 88.2 lb.ft
 Locked rotor torque : 230 %
 Breakdown torque : 260 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 16 s (hot)
 Service factor : 1.25
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 426 lb
 Moment of inertia : 9.1624 sq.ft.lb
 Noise level : 59 dB(A)

| | D.E. | N.D.E. |
|---------------------|---------|---------|
| Bearings | 6311 C3 | 6211 C3 |
| Regreasing interval | 20000 h | 20000 h |
| Grease amount | 18 g | 11 g |

| Load | Power factor | Efficiency (%) |
|------|--------------|----------------|
| 100% | 0.85 | 91.7 |
| 75% | 0.80 | 91.7 |
| 50% | 0.70 | 91.0 |

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #02012ET3E286JM-W22

Performed by

Checked