



Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Close Coupled Pump: Three-Phase - W01 (Rolled Steel) "JP" Type - TEFC - High Efficiency

Frame : 254/6JP
 Output : 20 HP
 Frequency : 60 Hz
 Poles : 4
 Full load speed : 1760 rpm
 Slip : 2.22 %
 Voltage : 208-230/460 V
 Rated current : 55.1-49.8/24.9 A
 Locked rotor current : 294/147 A
 Locked rotor current (I_L/I_n) : 5.9
 No-load current : 21.6/10.8 A
 Full load torque : 58.9 lb.ft
 Locked rotor torque : 210 %
 Breakdown torque : 270 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 12 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 197 lb
 Moment of inertia : 2.1528 sq.ft.lb
 Noise level : 68 dB(A)

| | D.E. | N.D.E. | Load | Power factor | Efficiency (%) |
|---------------------|-----------|-----------|------|--------------|----------------|
| Bearings | 6309 Z-C3 | 6208 Z-C3 | 100% | 0.83 | 91.0 |
| Regreasing interval | 20000 h | 20000 h | 75% | 0.78 | 91.0 |
| Grease amount | 13 g | 8 g | 50% | 0.67 | 91.0 |

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #02018EP3E256JP-S

Performed by

Checked