



Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

DATA SHEET

Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Close Coupled Pump : Three-Phase - "JM" Type - ODP - NEMA Premium

Frame : 256JM
 Output : 20 HP
 Frequency : 60 Hz
 Poles : 4
 Full load speed : 1770 rpm
 Slip : 1.67 %
 Voltage : 575 V
 Rated current : 19.8 A
 Locked rotor current : 124 A
 Locked rotor current (I_L/I_n) : 6.3
 No-load current : 9.60 A
 Full load torque : 58.5 lb.ft
 Locked rotor torque : 260 %
 Breakdown torque : 280 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 12 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP23
 Approximate weight : 295 lb
 Moment of inertia : 2.6198 sq.ft.lb
 Noise level : 60 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6309 Z-C3	6209 Z-C3	100%	0.82	93.0
Regreasing interval	20000 h	20000 h	75%	0.72	93.0
Grease amount	13 g	9 g	50%	0.63	91.7

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #02018OT3H256JM

Performed by

Checked