



# Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : Three-Phase : Explosion Proof - NEMA Premium

Frame : 256T  
 Output : 20 HP  
 Frequency : 60 Hz  
 Poles : 4  
 Full load speed : 1770 rpm  
 Slip : 1.67 %  
 Voltage : 208-230/460 V  
 Rated current : 55.3-50.0/25.0 A  
 Locked rotor current : 375/188 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 7.5  
 No-load current : 23.6/11.8 A  
 Full load torque : 58.5 lb.ft  
 Locked rotor torque : 300 %  
 Breakdown torque : 300 %  
 Design : B  
 Insulation class : F  
 Temperature rise : 80 K  
 Locked rotor time : 20 s (hot)  
 Service factor : 1.15  
 Duty cycle : S1  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : IP55  
 Approximate weight : 364 lb  
 Moment of inertia : 2.8889 sq.ft.lb  
 Noise level : 69 dB(A)

|                     | D.E.        | N.D.E.      |
|---------------------|-------------|-------------|
| Bearings            | 6309 2RS-C3 | 6209 2RS-C3 |
| Regreasing interval | ---         | ---         |
| Grease amount       | ---         | ---         |

| Load | Power factor | Efficiency (%) |
|------|--------------|----------------|
| 100% | 0.81         | 93.0           |
| 75%  | 0.75         | 92.4           |
| 50%  | 0.63         | 91.7           |

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #02018XT3ER256TC

Performed by

Checked