



Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : P-Base Motors : High Efficiency

Frame : 256HP
Output : 20 HP
Frequency : 60 Hz
Poles : 2
Full load speed : 3515 rpm
Slip : 2.36 %
Voltage : 230/460 V
Rated current : 47.0/23.5 A
Locked rotor current : 291/146 A
Locked rotor current (I_L/I_n) : 6.2
No-load current : 13.0/6.50 A
Full load torque : 29.5 lb.ft
Locked rotor torque : 190 %
Breakdown torque : 250 %
Design : B
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 15 s (hot)
Service factor : 1.25
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 280 lb
Moment of inertia : 1.1269 sq.ft.lb
Noise level : 75 dB(A)

	D.E.	N.D.E.
Bearings	6311 C3	6209 C3
Regreasing interval	5758 h	9224 h
Grease amount	18 g	9 g

Load	Power factor	Efficiency (%)
100%	0.89	90.2
75%	0.87	90.2
50%	0.81	89.5

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #02036EP3E256HP

Performed by

Checked