



Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : W22 NEMA Premium - Ball Bearings

Frame : 324/6T
Output : 25 HP
Frequency : 60 Hz
Poles : 8
Full load speed : 880 rpm
Slip : 2.22 %
Voltage : 575 V
Rated current : 28.7 A
Locked rotor current : 149 A
Locked rotor current (I_L/I_n) : 5.2
No-load current : 16.0 A
Full load torque : 147 lb.ft
Locked rotor torque : 200 %
Breakdown torque : 230 %
Design : B
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 23 s (hot)
Service factor : 1.25
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 509 lb
Moment of inertia : 11.919 sq.ft.lb
Noise level : 56 dB(A)

	D.E.	N.D.E.
Bearings	6312 C3	6212 C3
Regreasing interval	20000 h	20000 h
Grease amount	21 g	13 g

Load	Power factor	Efficiency (%)
100%	0.71	91.0
75%	0.64	91.0
50%	0.51	89.5

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #02509ET3H326T-W22

Performed by

Checked