



# Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : Three-Phase : Explosion Proof - High Efficiency

Frame : 326T  
 Output : 25 HP  
 Frequency : 60 Hz  
 Poles : 8  
 Full load speed : 880 rpm  
 Slip : 2.22 %  
 Voltage : 208-230/460 V  
 Rated current : 78.5-71.0/35.5 A  
 Locked rotor current : 362/181 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 5.1  
 No-load current : 40.8/20.4 A  
 Full load torque : 147 lb.ft  
 Locked rotor torque : 240 %  
 Breakdown torque : 240 %  
 Design : B  
 Insulation class : F  
 Temperature rise : 80 K  
 Locked rotor time : 29 s (hot)  
 Service factor : 1.15  
 Duty cycle : S1  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : IP54  
 Approximate weight : 673 lb  
 Moment of inertia : 11.919 sq.ft.lb  
 Noise level : 56 dB(A)

	D.E.	N.D.E.
Bearings	6312 2RS-C3	6212 2RS-C3
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.73	89.5
75%	0.65	88.5
50%	0.53	87.5

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #02509XP3E326T

Performed by

Checked