



Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Close Coupled Pump : Three-Phase - "JM" Type - ODP - High Efficiency

Frame : 284JM
 Output : 25 HP
 Frequency : 60 Hz
 Poles : 4
 Full load speed : 1765 rpm
 Slip : 1.94 %
 Voltage : 230/460 V
 Rated current : 60.2/30.1 A
 Locked rotor current : 361/181 A
 Locked rotor current (I_L/I_n) : 6.0
 No-load current : 23.0/11.5 A
 Full load torque : 73.4 lb.ft
 Locked rotor torque : 220 %
 Breakdown torque : 250 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 13 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP23
 Approximate weight : 324 lb
 Moment of inertia : 2.7672 sq.ft.lb
 Noise level : 62 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6311 Z-C3	6211 Z-C3	100%	0.84	91.7
Regreasing interval	20000 h	20000 h	75%	0.79	91.7
Grease amount	18 g	11 g	50%	0.70	91.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #02518OP3E284JM

Performed by

Checked