



Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Close Coupled Pump: Three-Phase - W22 "JM" Type - TEFC - High Efficiency

Frame : 284JM
 Output : 25 HP
 Frequency : 60 Hz
 Poles : 2
 Full load speed : 3530 rpm
 Slip : 1.94 %
 Voltage : 230/460 V
 Rated current : 58.0/29.0 A
 Locked rotor current : 348/174 A
 Locked rotor current (I_L/I_n) : 6.0
 No-load current : 14.0/7.00 A
 Full load torque : 36.7 lb.ft
 Locked rotor torque : 200 %
 Breakdown torque : 240 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 15 s (hot)
 Service factor : 1.25
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 344 lb
 Moment of inertia : 2.2895 sq.ft.lb
 Noise level : 72 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6311 C3	6211 C3	100%	0.90	91.0
Regreasing interval	14000 h	17000 h	75%	0.88	91.0
Grease amount	18 g	11 g	50%	0.83	91.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #02536EP3E284JM-W22

Performed by

Checked