



Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : W22 High Efficiency

Frame : 364/5T
 Output : 30 HP
 Frequency : 60 Hz
 Poles : 8
 Full load speed : 880 rpm
 Slip : 2.22 %
 Voltage : 208-230/460 V
 Rated current : 81.8-74.0/37.0 A
 Locked rotor current : 444/222 A
 Locked rotor current (I_L/I_n) : 6.0
 No-load current : 32.0/16.0 A
 Full load torque : 177 lb.ft
 Locked rotor torque : 160 %
 Breakdown torque : 220 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 17 s (hot)
 Service factor : 1.25
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 776 lb
 Moment of inertia : 23.455 sq.ft.lb
 Noise level : 60 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6314 C3	6314 C3	100%	0.82	91.0
Regreasing interval	20000 h	20000 h	75%	0.77	91.7
Grease amount	27 g	27 g	50%	0.67	91.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #03009EP3E364T-W22

Performed by

Checked