



# Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
Product line : P-Base Motors : High Efficiency

Frame : 286HPH  
Output : 30 HP  
Frequency : 60 Hz  
Poles : 2  
Full load speed : 3530 rpm  
Slip : 1.94 %  
Voltage : 230/460 V  
Rated current : 67.4/33.7 A  
Locked rotor current : 431/216 A  
Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 6.4  
No-load current : 16.2/8.10 A  
Full load torque : 44.0 lb.ft  
Locked rotor torque : 190 %  
Breakdown torque : 230 %  
Design : B  
Insulation class : F  
Temperature rise : 80 K  
Locked rotor time : 19 s (hot)  
Service factor : 1.25  
Duty cycle : S1  
Ambient temperature : -20°C - +40°C  
Altitude : 1000 m  
Degree of Protection : IP55  
Approximate weight : 364 lb  
Moment of inertia : 2.8284 sq.ft.lb  
Noise level : 75 dB(A)

	D.E.	N.D.E.
Bearings	6314 C3	6211 C3
Regreasing interval	3604 h	7113 h
Grease amount	27 g	11 g

Load	Power factor	Efficiency (%)
100%	0.90	91.0
75%	0.88	91.0
50%	0.84	90.2

Notes:  
Downloaded from <http://dealerselectric.com>  
Generated for Model #03036EP3E286HPH

Performed by

Checked