



Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : W22 NEMA Premium - Ball Bearings

Frame : 364/5T
 Output : 40 HP
 Frequency : 60 Hz
 Poles : 8
 Full load speed : 880 rpm
 Slip : 2.22 %
 Voltage : 208-230/460 V
 Rated current : 111-101/50.3 A
 Locked rotor current : 674/337 A
 Locked rotor current (I_L/I_n) : 6.7
 No-load current : 47.0/23.5 A
 Full load torque : 235 lb.ft
 Locked rotor torque : 170 %
 Breakdown torque : 230 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 18 s (hot)
 Service factor : 1.25
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 875 lb
 Moment of inertia : 29.040 sq.ft.lb
 Noise level : 60 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6314 C3	6314 C3	100%	0.81	92.4
Regreasing interval	20000 h	20000 h	75%	0.76	93.0
Grease amount	27 g	27 g	50%	0.66	92.4

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #04009ET3E365T-W22

Performed by

Checked