



Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : W22 Super Premium

Frame : 364/5T
 Output : 40 HP
 Frequency : 60 Hz
 Poles : 6
 Full load speed : 1185 rpm
 Slip : 1.25 %
 Voltage : 208-230/460 V
 Rated current : 108-97.8/48.9 A
 Locked rotor current : 822/411 A
 Locked rotor current (I_L/I_n) : 8.4
 No-load current : 46.0/23.0 A
 Full load torque : 175 lb.ft
 Locked rotor torque : 260 %
 Breakdown torque : 320 %
 Design : A
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 22 s (hot)
 Service factor : 1.25
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 875 lb
 Moment of inertia : 24.229 sq.ft.lb
 Noise level : 66 dB(A)

	D.E.	N.D.E.
Bearings	6314 C3	6314 C3
Regreasing interval	17000 h	17000 h
Grease amount	27 g	27 g

Load	Power factor	Efficiency (%)
100%	0.81	95.0
75%	0.76	94.5
50%	0.64	93.6

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #04012EG3E364T-W22

Performed by

Checked