



# Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : W22 Oil Well Pumping : High Slip - NEMA Design "D" - TEFC (IP55)

Frame : 364/5T  
 Output : 40 HP  
 Frequency : 60 Hz  
 Poles : 6  
 Full load speed : 1120 rpm  
 Slip : 6.67 %  
 Voltage : 208-230/460 V  
 Rated current : 109-97.8/48.9 A  
 Locked rotor current : 587/293 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 6.0  
 No-load current : 30.0/15.0 A  
 Full load torque : 185 lb.ft  
 Locked rotor torque : 280 %  
 Breakdown torque : 0 %  
 Design : D  
 Insulation class : F  
 Temperature rise : 80 K  
 Locked rotor time : 20 s (hot)  
 Service factor : 1.15  
 Duty cycle : S1  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : IP55  
 Approximate weight : 816 lb  
 Moment of inertia : 21.065 sq.ft.lb  
 Noise level : 66 dB(A)

	D.E.	N.D.E.
Bearings	6314 C3	6314 C3
Regreasing interval	17000 h	17000 h
Grease amount	27 g	27 g

Load	Power factor	Efficiency (%)
100%	0.88	87.5
75%	0.85	87.5
50%	0.77	85.5

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #04012ES3EOW365T-W22

Performed by

Checked