



Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

DATA SHEET

Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : Oil Well Pumping : High Slip - NEMA Design "D" - ODP

Frame : 365T
Output : 40 HP
Frequency : 60 Hz
Poles : 6
Full load speed : 1135 rpm
Slip : 5.42 %
Voltage : 208-230/460 V
Rated current : 113-103/51.3 A
Locked rotor current : 575/287 A
Locked rotor current (I_L/I_n) : 5.6
No-load current : 45.0/22.5 A
Full load torque : 183 lb.ft
Locked rotor torque : 280 %
Breakdown torque : 0 %
Design : D
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 31 s (hot)
Service factor : 1.00
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP23
Approximate weight : 750 lb
Moment of inertia : 21.780 sq.ft.lb
Noise level : 67 dB(A)

	D.E.	N.D.E.
Bearings	6314 C3	6314 C3
Regreasing interval	20000 h	20000 h
Grease amount	27 g	27 g

Load	Power factor	Efficiency (%)
100%	0.83	88.5
75%	0.76	88.5
50%	0.63	88.0

Notes:

Downloaded from <http://dealerselectric.com>
Generated for Model #04012OS3EOW365T

Performed by

Checked