



Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three-Phase: W22 IEEE-841™ Petrochem Motors - NEMA Premium® Efficiency

Frame : 364/5T
 Output : 40 HP
 Frequency : 60 Hz
 Poles : 6
 Full load speed : 1185 rpm
 Slip : 1.25 %
 Voltage : 460 V
 Rated current : 46.5 A
 Locked rotor current : 298 A
 Locked rotor current (I_L/I_n) : 6.4
 No-load current : 17.0 A
 Full load torque : 175 lb.ft
 Locked rotor torque : 200 %
 Breakdown torque : 240 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 21 s (hot)
 Service factor : 1.25
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 833 lb
 Moment of inertia : 29.040 sq.ft.lb
 Noise level : 66 dB(A)

| | D.E. | N.D.E. | Load | Power factor | Efficiency (%) |
|---------------------|---------|---------|------|--------------|----------------|
| Bearings | 6314 C3 | 6314 C3 | 100% | 0.86 | 94.1 |
| Regreasing interval | 17000 h | 17000 h | 75% | 0.82 | 93.6 |
| Grease amount | 27 g | 27 g | 50% | 0.73 | 93.6 |

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #04012ST3QIE364T-W22

Performed by

Checked