



Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : P-Base Motors : High Efficiency

Frame : 324HP
 Output : 40 HP
 Frequency : 60 Hz
 Poles : 4
 Full load speed : 1770 rpm
 Slip : 1.67 %
 Voltage : 230/460 V
 Rated current : 95.2/47.6 A
 Locked rotor current : 571/286 A
 Locked rotor current (I_L/I_n) : 6.0
 No-load current : 33.0/16.5 A
 Full load torque : 117 lb.ft
 Locked rotor torque : 230 %
 Breakdown torque : 230 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 25 s (hot)
 Service factor : 1.25
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 558 lb
 Moment of inertia : 6.9102 sq.ft.lb
 Noise level : 71 dB(A)

	D.E.	N.D.E.
Bearings	6314 C3	6212 C3
Regreasing interval	9790 h	10000 h
Grease amount	27 g	13 g

Load	Power factor	Efficiency (%)
100%	0.85	93.0
75%	0.82	93.0
50%	0.73	92.4

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #04018EP3E324HP

Performed by

Checked