



Dealers Industrial Equipment

No.:

Date: 23-SEP-2016

DATA SHEET

Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three-Phase: W22 IEEE-841™ Petrochem Motors - NEMA Premium® Efficiency

Frame : 404/5T
 Output : 50 HP
 Frequency : 60 Hz
 Poles : 8
 Full load speed : 880 rpm
 Slip : 2.22 %
 Voltage : 460 V
 Rated current : 60.0 A
 Locked rotor current : 408 A
 Locked rotor current (I_L/I_n) : 6.8
 No-load current : 25.0 A
 Full load torque : 294 lb.ft
 Locked rotor torque : 170 %
 Breakdown torque : 260 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 15 s (hot)
 Service factor : 1.25
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 1012 lb
 Moment of inertia : 34.625 sq.ft.lb
 Noise level : 60 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6316 C3	6314 C3	100%	0.83	93.0
Regreasing interval	20000 h	20000 h	75%	0.78	93.0
Grease amount	34 g	27 g	50%	0.68	93.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #05009ST3QIE404T-W22

Performed by

Checked