



Dealers Industrial Equipment

No.:

Date: 27-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three-Phase : Explosion Proof - NEMA Premium

Frame : 326TS
 Output : 50 HP
 Frequency : 60 Hz
 Poles : 2
 Full load speed : 3550 rpm
 Slip : 1.39 %
 Voltage : 575 V
 Rated current : 44.4 A
 Locked rotor current : 320 A
 Locked rotor current (I_L/I_n) : 7.2
 No-load current : 11.8 A
 Full load torque : 73.0 lb.ft
 Locked rotor torque : 210 %
 Breakdown torque : 210 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 33 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 728 lb
 Moment of inertia : 5.4187 sq.ft.lb
 Noise level : 81 dB(A)

	D.E.	N.D.E.
Bearings	6312 2RS-C3	6212 2RS-C3
Regreasing interval	---	---
Grease amount	---	---

Load	Power factor	Efficiency (%)
100%	0.89	94.1
75%	0.88	93.6
50%	0.82	92.4

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #05036XT3H326TS

Performed by

Checked