



Dealers Industrial Equipment

No.:

Date: 27-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three-Phase: W22 IE2 IEC Tru-Metric - TEFC (IP55) Cast Iron Frame

Frame : 280S/M
 Output : 75 HP
 Frequency : 60 Hz
 Poles : 8
 Full load speed : 890 rpm
 Slip : 1.11 %
 Voltage : 460 V
 Rated current : 91.3 A
 Locked rotor current : 593 A
 Locked rotor current (I_L/I_n) : 6.5
 No-load current : 44.7 A
 Full load torque : 437 lb.ft
 Locked rotor torque : 230 %
 Breakdown torque : 230 %
 Design : ---
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 24 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 1566 lb
 Moment of inertia : 74.966 sq.ft.lb
 Noise level : 63 dB(A)

	D.E.	N.D.E.
Bearings	6316 C3	6316 C3
Regreasing interval	20000 h	20000 h
Grease amount	34 g	34 g

Load	Power factor	Efficiency (%)
100%	0.80	94.5
75%	0.74	94.1
50%	0.61	93.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #05509EP3Y315S/M-W22

Performed by

Checked