



Dealers Industrial Equipment

No.:

Date: 27-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Close Coupled Pump: Three-Phase - W22 "JP" Type - TEFC - NEMA Premium

Frame : 404/5JP
 Output : 60 HP
 Frequency : 60 Hz
 Poles : 6
 Full load speed : 1185 rpm
 Slip : 1.25 %
 Voltage : 208-230/460 V
 Rated current : 154-139/69.5 A
 Locked rotor current : 987/493 A
 Locked rotor current (I_L/I_n) : 7.1
 No-load current : 50.0/25.0 A
 Full load torque : 262 lb.ft
 Locked rotor torque : 200 %
 Breakdown torque : 230 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 20 s (hot)
 Service factor : 1.25
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 1036 lb
 Moment of inertia : 36.858 sq.ft.lb
 Noise level : 68 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6314 C3	6314 C3	100%	0.86	94.5
Regreasing interval	17000 h	17000 h	75%	0.82	94.5
Grease amount	27 g	27 g	50%	0.74	94.1

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #06012ET3E404JP-W22

Performed by

Checked