



# Dealers Industrial Equipment

No.:

Date: 27-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : Three-Phase : Explosion Proof - NEMA Premium

Frame : 404/5T  
 Output : 60 HP  
 Frequency : 60 Hz  
 Poles : 6  
 Full load speed : 1185 rpm  
 Slip : 1.25 %  
 Voltage : 208-230/460 V  
 Rated current : 156-141/70.3 A  
 Locked rotor current : 970/485 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 6.9  
 No-load current : 50.0/25.0 A  
 Full load torque : 262 lb.ft  
 Locked rotor torque : 250 %  
 Breakdown torque : 270 %  
 Design : B  
 Insulation class : F  
 Temperature rise : 80 K  
 Locked rotor time : 29 s (hot)  
 Service factor : 1.15  
 Duty cycle : S1  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : IP55  
 Approximate weight : 1213 lb  
 Moment of inertia : 36.858 sq.ft.lb  
 Noise level : 65 dB(A)

	D.E.	N.D.E.
Bearings	6217 C3	6314 C3
Regreasing interval	13507 h	14267 h
Grease amount	21 g	27 g

Load	Power factor	Efficiency (%)
100%	0.85	94.5
75%	0.82	94.5
50%	0.73	93.6

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #06012XT3E404T

Performed by

Checked