



Dealers Industrial Equipment

No.:

Date: 27-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Close Coupled Pump : Three-Phase - "JM" Type - ODP - High Efficiency

Frame : 364JM
 Output : 60 HP
 Frequency : 60 Hz
 Poles : 4
 Full load speed : 1780 rpm
 Slip : 1.11 %
 Voltage : 460 V
 Rated current : 70.2 A
 Locked rotor current : 428 A
 Locked rotor current (I_L/I_n) : 6.1
 No-load current : 24.0 A
 Full load torque : 175 lb.ft
 Locked rotor torque : 220 %
 Breakdown torque : 260 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 16 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP23
 Approximate weight : 633 lb
 Moment of inertia : 12.456 sq.ft.lb
 Noise level : 67 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6314 C3	6314 C3	100%	0.86	93.6
Regreasing interval	20000 h	20000 h	75%	0.83	93.6
Grease amount	27 g	27 g	50%	0.73	92.4

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #06018OP3G364JM

Performed by

Checked