



Dealers Industrial Equipment

No.:

Date: 27-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : W22 Super Premium

Frame : 364/5TS
Output : 60 HP
Frequency : 60 Hz
Poles : 2
Full load speed : 3570 rpm
Slip : 0.83 %
Voltage : 208-230/460 V
Rated current : 148-134/66.8 A
Locked rotor current : 1060/528 A
Locked rotor current (I_L/I_n) : 7.9
No-load current : 44.0/22.0 A
Full load torque : 87.1 lb.ft
Locked rotor torque : 240 %
Breakdown torque : 320 %
Design : A
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 25 s (hot)
Service factor : 1.25
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 926 lb
Moment of inertia : 8.6064 sq.ft.lb
Noise level : 79 dB(A)

	D.E.	N.D.E.
Bearings	6314 C3	6314 C3
Regreasing interval	4000 h	4000 h
Grease amount	27 g	27 g

Load	Power factor	Efficiency (%)
100%	0.89	95.0
75%	0.86	94.5
50%	0.79	93.0

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #06036EG3E364TS-W22

Performed by

Checked