



Dealers Industrial Equipment

No.:

Date: 27-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Close Coupled Pump: Three-Phase - W22 "JP" Type - TEFC - High Efficiency

Frame : 324/6JP
 Output : 60 HP
 Frequency : 60 Hz
 Poles : 2
 Full load speed : 3550 rpm
 Slip : 1.39 %
 Voltage : 208-230/460 V
 Rated current : 153-138/69.0 A
 Locked rotor current : 828/414 A
 Locked rotor current (I_L/I_n) : 6.0
 No-load current : 36.0/18.0 A
 Full load torque : 87.6 lb.ft
 Locked rotor torque : 210 %
 Breakdown torque : 230 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 17 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 584 lb
 Moment of inertia : 5.3212 sq.ft.lb
 Noise level : 76 dB(A)

| | D.E. | N.D.E. |
|---------------------|---------|---------|
| Bearings | 6312 C3 | 6212 C3 |
| Regreasing interval | 12000 h | 15000 h |
| Grease amount | 21 g | 13 g |

| Load | Power factor | Efficiency (%) |
|------|--------------|----------------|
| 100% | 0.88 | 93.0 |
| 75% | 0.87 | 93.0 |
| 50% | 0.82 | 92.4 |

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #06036EP3E326JP-W22

Performed by

Checked