



# Dealers Industrial Equipment

No.:

Date: 27-SEP-2016

## DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :  
 Product line : Close Coupled Pump : Three-Phase - "JP" Type - ODP - NEMA Premium

Frame : 326JP  
 Output : 60 HP  
 Frequency : 60 Hz  
 Poles : 2  
 Full load speed : 3555 rpm  
 Slip : 1.25 %  
 Voltage : 575 V  
 Rated current : 56.8 A  
 Locked rotor current : 352 A  
 Locked rotor current (I<sub>L</sub>/I<sub>n</sub>) : 6.2  
 No-load current : 14.4 A  
 Full load torque : 87.4 lb.ft  
 Locked rotor torque : 200 %  
 Breakdown torque : 260 %  
 Design : B  
 Insulation class : F  
 Temperature rise : 80 K  
 Locked rotor time : 24 s (hot)  
 Service factor : 1.15  
 Duty cycle : S1  
 Ambient temperature : -20°C - +40°C  
 Altitude : 1000 m  
 Degree of Protection : IP23  
 Approximate weight : 582 lb  
 Moment of inertia : 4.3635 sq.ft.lb  
 Noise level : 75 dB(A)

|                     | D.E.      | N.D.E.    |
|---------------------|-----------|-----------|
| Bearings            | 6312 Z-C3 | 6212 Z-C3 |
| Regreasing interval | 19658 h   | 20000 h   |
| Grease amount       | 21 g      | 13 g      |

| Load | Power factor | Efficiency (%) |
|------|--------------|----------------|
| 100% | 0.85         | 93.6           |
| 75%  | 0.84         | 93.6           |
| 50%  | 0.77         | 93.0           |

Notes:  
 Downloaded from <http://dealerselectric.com>  
 Generated for Model #06036OT3H326JP

Performed by

Checked