



Dealers Industrial Equipment

No.:

Date: 27-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three-Phase: W22 Crusher Duty TEFC (IP55)

Frame : 444/5T
 Output : 75 HP
 Frequency : 60 Hz
 Poles : 8
 Full load speed : 885 rpm
 Slip : 1.67 %
 Voltage : 460 V
 Rated current : 92.8 A
 Locked rotor current : 520 A
 Locked rotor current (I_L/I_n) : 5.6
 No-load current : 36.0 A
 Full load torque : 439 lb.ft
 Locked rotor torque : 170 %
 Breakdown torque : 200 %
 Design : A
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 20 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 1444 lb
 Moment of inertia : 73.625 sq.ft.lb
 Noise level : 63 dB(A)

	D.E.	N.D.E.
Bearings	NU-319 C3	6316 C3
Regreasing interval	15000 h	20000 h
Grease amount	45 g	34 g

Load	Power factor	Efficiency (%)
100%	0.80	93.0
75%	0.76	93.0
50%	0.67	93.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #07509EP3GKD444T-W22

Performed by

Checked