



Dealers Industrial Equipment

No.:

Date: 27-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : Three-Phase : Explosion Proof - High Efficiency

Frame : 444T
Output : 75 HP
Frequency : 60 Hz
Poles : 8
Full load speed : 890 rpm
Slip : 1.11 %
Voltage : 208-230/460 V
Rated current : 200-181/90.5 A
Locked rotor current : 1100/552 A
Locked rotor current (I_L/I_n) : 6.1
No-load current : 72.5/36.3 A
Full load torque : 437 lb.ft
Locked rotor torque : 170 %
Breakdown torque : 210 %
Design : B
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 28 s (hot)
Service factor : 1.15
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP54
Approximate weight : 1911 lb
Moment of inertia : 73.625 sq.ft.lb
Noise level : 64 dB(A)

	D.E.	N.D.E.
Bearings	6219 C3	6316 C3
Regreasing interval	15247 h	15904 h
Grease amount	27 g	34 g

Load	Power factor	Efficiency (%)
100%	0.82	93.0
75%	0.78	92.4
50%	0.69	91.7

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #07509XP3E444T

Performed by

Checked