



Dealers Industrial Equipment

No.:

Date: 27-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : W22 Super Premium

Frame : 364/5T
Output : 75 HP
Frequency : 60 Hz
Poles : 4
Full load speed : 1780 rpm
Slip : 1.11 %
Voltage : 208-230/460 V
Rated current : 192-174/86.8 A
Locked rotor current : 1460/729 A
Locked rotor current (I_L/I_n) : 8.4
No-load current : 76.0/38.0 A
Full load torque : 218 lb.ft
Locked rotor torque : 280 %
Breakdown torque : 320 %
Design : A
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 16 s (hot)
Service factor : 1.25
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 919 lb
Moment of inertia : 16.851 sq.ft.lb
Noise level : 67 dB(A)

	D.E.	N.D.E.
Bearings	6314 C3	6314 C3
Regreasing interval	12000 h	12000 h
Grease amount	27 g	27 g

Load	Power factor	Efficiency (%)
100%	0.83	95.8
75%	0.78	95.4
50%	0.68	94.5

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #07518EG3E365T-W22

Performed by

Checked