



Dealers Industrial Equipment

No.:

Date: 27-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three-Phase : Explosion Proof - NEMA Premium

Frame : 364/5T
 Output : 75 HP
 Frequency : 60 Hz
 Poles : 4
 Full load speed : 1780 rpm
 Slip : 1.11 %
 Voltage : 208-230/460 V
 Rated current : 184-166/83.2 A
 Locked rotor current : 1160/582 A
 Locked rotor current (I_L/I_n) : 7.0
 No-load current : 56.0/28.0 A
 Full load torque : 218 lb.ft
 Locked rotor torque : 240 %
 Breakdown torque : 290 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 16 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 937 lb
 Moment of inertia : 23.251 sq.ft.lb
 Noise level : 75 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6314 C3	6314 C3	100%	0.87	95.4
Regreasing interval	9789 h	9789 h	75%	0.83	95.0
Grease amount	27 g	27 g	50%	0.74	94.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #07518XT3E365TC

Performed by

Checked