



Dealers Industrial Equipment

No.:

Date: 27-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : Three-Phase : Explosion Proof - NEMA Premium

Frame : 364/5TS
Output : 75 HP
Frequency : 60 Hz
Poles : 2
Full load speed : 3560 rpm
Slip : 1.11 %
Voltage : 575 V
Rated current : 65.9 A
Locked rotor current : 461 A
Locked rotor current (I_L/I_n) : 7.0
No-load current : 17.6 A
Full load torque : 109 lb.ft
Locked rotor torque : 230 %
Breakdown torque : 260 %
Design : B
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 18 s (hot)
Service factor : 1.15
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 1025 lb
Moment of inertia : 9.9623 sq.ft.lb
Noise level : 85 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6314 C3	6314 C3	100%	0.89	94.1
Regreasing interval	3604 h	3604 h	75%	0.87	94.1
Grease amount	27 g	27 g	50%	0.81	93.0

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #07536XT3H365TS

Performed by

Checked