



Dealers Industrial Equipment

No.:

Date: 27-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : Three-Phase : Explosion Proof - NEMA Premium

Frame : 444/5T
Output : 100 HP
Frequency : 60 Hz
Poles : 6
Full load speed : 1190 rpm
Slip : 0.83 %
Voltage : 208-230/460 V
Rated current : 267-242/121 A
Locked rotor current : 1640/822 A
Locked rotor current (I_L/I_n) : 6.8
No-load current : 97.5/48.8 A
Full load torque : 435 lb.ft
Locked rotor torque : 230 %
Breakdown torque : 260 %
Design : B
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 49 s (hot)
Service factor : 1.15
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 1896 lb
Moment of inertia : 87.260 sq.ft.lb
Noise level : 70 dB(A)

	D.E.	N.D.E.
Bearings	6219 C3	6316 C3
Regreasing interval	12202 h	12823 h
Grease amount	27 g	34 g

Load	Power factor	Efficiency (%)
100%	0.82	95.0
75%	0.76	95.0
50%	0.66	94.1

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #10012XT3E444T

Performed by

Checked