



Dealers Industrial Equipment

No.:

Date: 27-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Close Coupled Pump: Three-Phase - W22 "JP" Type - TEFC - High Efficiency

Frame : 404/5JP
 Output : 100 HP
 Frequency : 60 Hz
 Poles : 4
 Full load speed : 1775 rpm
 Slip : 1.39 %
 Voltage : 230/460 V
 Rated current : 226/113 A
 Locked rotor current : 1380/689 A
 Locked rotor current (I_L/I_n) : 6.1
 No-load current : 66.0/33.0 A
 Full load torque : 292 lb.ft
 Locked rotor torque : 210 %
 Breakdown torque : 240 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 14 s (hot)
 Service factor : 1.25
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 1094 lb
 Moment of inertia : 27.403 sq.ft.lb
 Noise level : 70 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6314 C3	6314 C3	100%	0.88	94.5
Regreasing interval	12000 h	12000 h	75%	0.86	94.5
Grease amount	27 g	27 g	50%	0.80	94.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #10018EP3E405JP-W22

Performed by

Checked