



Dealers Industrial Equipment

No.:

Date: 28-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : W22 High Efficiency

Frame : 445/7T
 Output : 125 HP
 Frequency : 60 Hz
 Poles : 8
 Full load speed : 885 rpm
 Slip : 1.67 %
 Voltage : 230/460 V
 Rated current : 302/151 A
 Locked rotor current : 1750/876 A
 Locked rotor current (I_L/I_n) : 5.8
 No-load current : 120/60.0 A
 Full load torque : 732 lb.ft
 Locked rotor torque : 180 %
 Breakdown torque : 200 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 15 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 1806 lb
 Moment of inertia : 103.62 sq.ft.lb
 Noise level : 63 dB(A)

	D.E.	N.D.E.
Bearings	6319 C3	6316 C3
Regreasing interval	17000 h	20000 h
Grease amount	45 g	34 g

Load	Power factor	Efficiency (%)
100%	0.80	93.6
75%	0.76	94.1
50%	0.67	93.6

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #12509EP3E447T-W22

Performed by

Checked