



Dealers Industrial Equipment

No.:

Date: 28-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : W22 High Efficiency

Frame : 445/7T
Output : 125 HP
Frequency : 60 Hz
Poles : 8
Full load speed : 885 rpm
Slip : 1.67 %
Voltage : 460 V
Rated current : 151 A
Locked rotor current : 876 A
Locked rotor current (I_L/I_n) : 5.8
No-load current : 60.0 A
Full load torque : 732 lb.ft
Locked rotor torque : 180 %
Breakdown torque : 200 %
Design : B
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 15 s (hot)
Service factor : 1.15
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 1806 lb
Moment of inertia : 103.62 sq.ft.lb
Noise level : 63 dB(A)

	D.E.	N.D.E.
Bearings	6319 C3	6316 C3
Regreasing interval	17000 h	20000 h
Grease amount	45 g	34 g

Load	Power factor	Efficiency (%)
100%	0.80	93.6
75%	0.76	94.1
50%	0.67	93.6

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #12509EP3G447T-W22

Performed by

Checked