



Dealers Industrial Equipment

No.:

Date: 28-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : W22 Super Premium

Frame : 444/5T
Output : 125 HP
Frequency : 60 Hz
Poles : 6
Full load speed : 1190 rpm
Slip : 0.83 %
Voltage : 460 V
Rated current : 152 A
Locked rotor current : 1160 A
Locked rotor current (I_L/I_n) : 7.6
No-load current : 72.0 A
Full load torque : 544 lb.ft
Locked rotor torque : 240 %
Breakdown torque : 260 %
Design : A
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 25 s (hot)
Service factor : 1.25
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 1945 lb
Moment of inertia : 113.81 sq.ft.lb
Noise level : 69 dB(A)

	D.E.	N.D.E.
Bearings	6319 C3	6316 C3
Regreasing interval	13000 h	16000 h
Grease amount	45 g	34 g

Load	Power factor	Efficiency (%)
100%	0.80	95.8
75%	0.74	95.8
50%	0.62	95.0

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #12512EG3G445T-W22

Performed by

Checked