



Dealers Industrial Equipment

No.:

Date: 28-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : ODP – Open Induction Motors – NEMA Premium Efficiency

Frame : 444/5T
 Output : 125 HP
 Frequency : 60 Hz
 Poles : 6
 Full load speed : 1185 rpm
 Slip : 1.25 %
 Voltage : 460 V
 Rated current : 158 A
 Locked rotor current : 1060 A
 Locked rotor current (I_L/I_n) : 6.7
 No-load current : 76.0 A
 Full load torque : 547 lb.ft
 Locked rotor torque : 240 %
 Breakdown torque : 240 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 20 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP23
 Approximate weight : 1740 lb
 Moment of inertia : 70.899 sq.ft.lb
 Noise level : 78 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6319 C3	6316 C3	100%	0.78	95.0
Regreasing interval	20000 h	20000 h	75%	0.72	95.0
Grease amount	45 g	34 g	50%	0.60	94.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #12512OT3G445T

Performed by

Checked