



Dealers Industrial Equipment

No.:

Date: 28-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Fire Pump Motors - ODP Three Phase - Foot Mount and Flange Mount

Frame : 404/5T
 Output : 125 HP
 Frequency : 60 Hz
 Poles : 4
 Full load speed : 1775 rpm
 Slip : 1.39 %
 Voltage : 460 V
 Rated current : 146 A
 Locked rotor current : 905 A
 Locked rotor current (I_L/I_n) : 6.2
 No-load current : 44.0 A
 Full load torque : 365 lb.ft
 Locked rotor torque : 240 %
 Breakdown torque : 260 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 11 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP23
 Approximate weight : 1052 lb
 Moment of inertia : 20.760 sq.ft.lb
 Noise level : 69 dB(A)

| | D.E. | N.D.E. |
|---------------------|---------|---------|
| Bearings | 6316 C3 | 6314 C3 |
| Regreasing interval | 20000 h | 20000 h |
| Grease amount | 34 g | 27 g |

| Load | Power factor | Efficiency (%) |
|------|--------------|----------------|
| 100% | 0.85 | 94.5 |
| 75% | 0.83 | 94.5 |
| 50% | 0.75 | 94.1 |

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #12518OP3GFP405TC

Performed by

Checked