



Dealers Industrial Equipment

No.:

Date: 28-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : W22 Super Premium

Frame : 444/5TS
Output : 125 HP
Frequency : 60 Hz
Poles : 2
Full load speed : 3580 rpm
Slip : 0.56 %
Voltage : 460 V
Rated current : 136 A
Locked rotor current : 1120 A
Locked rotor current (I_L/I_n) : 8.2
No-load current : 46.0 A
Full load torque : 181 lb.ft
Locked rotor torque : 230 %
Breakdown torque : 310 %
Design : A
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 44 s (hot)
Service factor : 1.25
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 1680 lb
Moment of inertia : 31.269 sq.ft.lb
Noise level : 81 dB(A)

	D.E.	N.D.E.
Bearings	6314 C3	6314 C3
Regreasing interval	4000 h	4000 h
Grease amount	27 g	27 g

Load	Power factor	Efficiency (%)
100%	0.87	95.8
75%	0.84	95.4
50%	0.76	94.1

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #12536EG3G444TS-W22

Performed by

Checked