



Dealers Industrial Equipment

No.:

Date: 28-SEP-2016

DATA SHEET

Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three-Phase: W22 IE2 IEC Tru-Metric - TEFC (IP55) Cast Iron Frame

Frame : 315L
 Output : 175 HP
 Frequency : 60 Hz
 Poles : 8
 Full load speed : 890 rpm
 Slip : 1.11 %
 Voltage : 460 V
 Rated current : 217 A
 Locked rotor current : 1540 A
 Locked rotor current (I_L/I_n) : 7.1
 No-load current : 107 A
 Full load torque : 1019 lb.ft
 Locked rotor torque : 230 %
 Breakdown torque : 250 %
 Design : ---
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 20 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 2981 lb
 Moment of inertia : 312.96 sq.ft.lb
 Noise level : 71 dB(A)

	D.E.	N.D.E.
Bearings	6319 C3	6316 C3
Regreasing interval	17000 h	20000 h
Grease amount	45 g	34 g

Load	Power factor	Efficiency (%)
100%	0.80	95.4
75%	0.74	95.0
50%	0.61	94.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #13209EP3Y315L-W22

Performed by

Checked