



Dealers Industrial Equipment

No.:

Date: 28-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : P-Base Motors : High Efficiency

Frame : 445HP
Output : 150 HP
Frequency : 60 Hz
Poles : 4
Full load speed : 1780 rpm
Slip : 1.11 %
Voltage : 460 V
Rated current : 167 A
Locked rotor current : 1070 A
Locked rotor current (I_L/I_n) : 6.4
No-load current : 45.0 A
Full load torque : 437 lb.ft
Locked rotor torque : 220 %
Breakdown torque : 230 %
Design : B
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 27 s (hot)
Service factor : 1.15
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 1665 lb
Moment of inertia : 57.163 sq.ft.lb
Noise level : 76 dB(A)

	D.E.	N.D.E.
Bearings	6319 C3	6316 C3
Regreasing interval	3519 h	4284 h
Grease amount	45 g	34 g

Load	Power factor	Efficiency (%)
100%	0.87	95.0
75%	0.84	95.0
50%	0.78	94.1

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #15018EP3G445HP

Performed by

Checked