



Dealers Industrial Equipment

No.:

Date: 28-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three-Phase : Explosion Proof - NEMA Premium

Frame : 444/5T
 Output : 150 HP
 Frequency : 60 Hz
 Poles : 4
 Full load speed : 1780 rpm
 Slip : 1.11 %
 Voltage : 575 V
 Rated current : 136 A
 Locked rotor current : 857 A
 Locked rotor current (I_L/I_n) : 6.3
 No-load current : 41.6 A
 Full load torque : 437 lb.ft
 Locked rotor torque : 220 %
 Breakdown torque : 250 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 22 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 2095 lb
 Moment of inertia : 66.690 sq.ft.lb
 Noise level : 76 dB(A)

	D.E.	N.D.E.
Bearings	6219 C3	6316 C3
Regreasing interval	8033 h	8569 h
Grease amount	27 g	34 g

Load	Power factor	Efficiency (%)
100%	0.85	95.8
75%	0.81	95.8
50%	0.72	95.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #15018XT3H445T

Performed by

Checked