



Dealers Industrial Equipment

No.:

Date: 28-SEP-2016

DATA SHEET

Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three-Phase: W22 IE2 IEC Tru-Metric - TEFC (IP55) Cast Iron Frame

Frame : 315S/M
 Output : 250 HP
 Frequency : 60 Hz
 Poles : 2
 Full load speed : 3580 rpm
 Slip : 0.56 %
 Voltage : 460 V
 Rated current : 270 A
 Locked rotor current : 2300 A
 Locked rotor current (I_L/I_n) : 8.5
 No-load current : 89.0 A
 Full load torque : 362 lb.ft
 Locked rotor torque : 250 %
 Breakdown torque : 350 %
 Design : ---
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 16 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 2276 lb
 Moment of inertia : 33.799 sq.ft.lb
 Noise level : 81 dB(A)

	D.E.	N.D.E.
Bearings	6314 C3	6314 C3
Regreasing interval	4000 h	4000 h
Grease amount	27 g	27 g

Load	Power factor	Efficiency (%)
100%	0.90	95.4
75%	0.86	95.0
50%	0.76	94.1

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #18536EP3Y315S/M-W22

Performed by

Checked