



Dealers Industrial Equipment

No.:

Date: 28-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three-Phase: W22 Crusher Duty TEFC (IP55)

Frame : 504/5Z
 Output : 200 HP
 Frequency : 60 Hz
 Poles : 6
 Full load speed : 1190 rpm
 Slip : 0.83 %
 Voltage : 575 V
 Rated current : 189 A
 Locked rotor current : 1130 A
 Locked rotor current (I_L/I_n) : 6.0
 No-load current : 64.0 A
 Full load torque : 871 lb.ft
 Locked rotor torque : 200 %
 Breakdown torque : 210 %
 Design : A
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 19 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 2368 lb
 Moment of inertia : 133.62 sq.ft.lb
 Noise level : 70 dB(A)

	D.E.	N.D.E.
Bearings	NU-322 C3	6316 C3
Regreasing interval	7000 h	16000 h
Grease amount	60 g	34 g

Load	Power factor	Efficiency (%)
100%	0.84	95.0
75%	0.81	95.0
50%	0.73	95.0

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #20012EP3HKD505Z-W22

Performed by

Checked