



Dealers Industrial Equipment

No.:

Date: 28-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : Three-Phase : Explosion Proof - NEMA Premium

Frame : 447T
 Output : 200 HP
 Frequency : 60 Hz
 Poles : 6
 Full load speed : 1190 rpm
 Slip : 0.83 %
 Voltage : 460 V
 Rated current : 249 A
 Locked rotor current : 1940 A
 Locked rotor current (I_L/I_n) : 7.8
 No-load current : 125 A
 Full load torque : 871 lb.ft
 Locked rotor torque : 270 %
 Breakdown torque : 280 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 14 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP55
 Approximate weight : 2615 lb
 Moment of inertia : 133.62 sq.ft.lb
 Noise level : 73 dB(A)

	D.E.	N.D.E.
Bearings	6319 C3	6316 C3
Regreasing interval	11094 h	12823 h
Grease amount	45 g	34 g

Load	Power factor	Efficiency (%)
100%	0.79	95.8
75%	0.73	95.4
50%	0.60	94.5

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #20012XT3G447T

Performed by

Checked