



Dealers Industrial Equipment

No.:

Date: 28-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : W22 NEMA Premium - Ball Bearings

Frame : 445/7TS
Output : 200 HP
Frequency : 60 Hz
Poles : 2
Full load speed : 3570 rpm
Slip : 0.83 %
Voltage : 460 V
Rated current : 219 A
Locked rotor current : 1420 A
Locked rotor current (I_L/I_n) : 6.5
No-load current : 45.0 A
Full load torque : 290 lb.ft
Locked rotor torque : 210 %
Breakdown torque : 230 %
Design : B
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 14 s (hot)
Service factor : 1.15
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 1914 lb
Moment of inertia : 44.677 sq.ft.lb
Noise level : 81 dB(A)

| | D.E. | N.D.E. |
|---------------------|---------|---------|
| Bearings | 6314 C3 | 6314 C3 |
| Regreasing interval | 4000 h | 4000 h |
| Grease amount | 27 g | 27 g |

| Load | Power factor | Efficiency (%) |
|------|--------------|----------------|
| 100% | 0.90 | 95.4 |
| 75% | 0.89 | 95.4 |
| 50% | 0.86 | 95.0 |

Notes:
Downloaded from <http://dealerselectric.com>
Generated for Model #20036ET3G447TS-W22

Performed by

Checked