



Dealers Industrial Equipment

No.:

Date: 28-SEP-2016

DATA SHEET Three-phase induction motor - Squirrel cage rotor

Customer :
 Product line : ODP – Open Induction Motors – NEMA Premium Efficiency

Frame : 444TS
 Output : 200 HP
 Frequency : 60 Hz
 Poles : 2
 Full load speed : 3575 rpm
 Slip : 0.69 %
 Voltage : 460 V
 Rated current : 223 A
 Locked rotor current : 1450 A
 Locked rotor current (I_L/I_n) : 6.5
 No-load current : 64.0 A
 Full load torque : 290 lb.ft
 Locked rotor torque : 190 %
 Breakdown torque : 250 %
 Design : B
 Insulation class : F
 Temperature rise : 80 K
 Locked rotor time : 20 s (hot)
 Service factor : 1.15
 Duty cycle : S1
 Ambient temperature : -20°C - +40°C
 Altitude : 1000 m
 Degree of Protection : IP23
 Approximate weight : 1537 lb
 Moment of inertia : 25.689 sq.ft.lb
 Noise level : 88 dB(A)

	D.E.	N.D.E.
Bearings	6314 C3	6314 C3
Regreasing interval	14418 h	14418 h
Grease amount	27 g	27 g

Load	Power factor	Efficiency (%)
100%	0.89	95.0
75%	0.87	94.5
50%	0.81	93.6

Notes:
 Downloaded from <http://dealerselectric.com>
 Generated for Model #20036OT3G444TS

Performed by

Checked